BPA F 6420.24

U.S. DEPARTMENT OF ENERGY BONNEVILLE POWER ADMINISTRATION TRANSMISSION BUSINESS LINE INTERCONNECTION STUDY REQUEST

Electronic Form

WHO SHOULD FILE THIS APPLICATION:

Any customer expressing an interest in interconnecting generation. This application should be completed as soon as possible and returned to the BPA Account Executive in order to begin processing the request.

INFORMATION:

This application will be used by the Bonneville Power Administration to perform Preliminary and Detailed Interconnection Studies to determine the Interface requirements at the customer's Point of Interconnection. The applicant should attempt to fill in as much of the form as possible. The applicant will receive a preliminary estimate for the utility interface requirements that may be used in calculating the overall Project requirements.

OWNER/PROJECT SI	PONSOR INFORMATION							
Owner of Project			Project Sponsor					
Company		Company						
Contact		Contact	Contact					
Mailing Address:		Mailing Address:	Mailing Address:					
City/State/ 9 Digit Zip Code		City/State/ 9 Digit Zip Co	City/State/ 9 Digit Zip Code					
		·						
Phone Number		Phone Number						
		•						
PROJECT DESIGN/EI	NGINEERING ARCHITECT (As	applicable)						
Company								
Mailing Address								
City	County	State	9 Digit Zip Code					
	·	•	·					
Phone Number		Contact						
		·						
ELECTRICAL CONTR	ACTOR (As applicable)							
Company								
Mailing Address								
City	County	State	9 Digit Zip Code					
Phone Number		Contact						
		·						

BPA F 6420.24 (Page 2)

GENERATOR DATA								
Manufacturer (If available)			Model	:				
TYPE								
Synchronous	Induction	Phases:Single	Three	Freque	ncy (Hz)			
Rated Output:		Kilowatts		ŀ	(ilovolt-Ampere			
Rated Power Factor	%	Rated Voltage	Volts Rate	ed Amperes:	Amps			
Energy Source (Gas, Hydro, Wind, Co-Gen., Geothermal, etc.):								
Plant Load (Auxiliaries)			kW		KVAR			
Net Maximum Power to BPA			kW		KVAR			
Operating Dates and Capacit	y:		kW		Date			
Ultimate Output (Max.)			kW		Date			
Estimated Peak and Energy Production (Ultimate Output)								
January			peak kw		kwh			
February			peak kw		kwh			
March			peak kw		kwh			
April			peak kw		kwh			
May			peak kw		kwh			
June			peak kw		kwh			
July			peak kw		kwh			
August			peak kw		kwh			
September			peak kw		kwh			
October			peak kw		kwh			
November			peak kw		kwh			
December			peak kw		kwh			
PROJECT LOCATION								
STATE	COUNTY		NEAREST COMMU	NITY				
TOWNSHIP	RANGE		SECTION					
STREET ADDRESS								
DATE		SIGNATURE						
-		1						
NAME (Please Print or Type)		TITLE						
**ATTACH MAP SHOWING PROJECT BOUNDARIES AND SUBSTATION LOCATION **								
ATTACH MAR SHOWING PROJECT DOUNDARIES AND SUBSTATION LOCATION								

BPA F 6420.24 (Page 3)

ELECTRICAL AND SYNCHRONOUS MACHINE INFORMATION

1. Electrical One-Line Diagram of the generation Project that includes proposed protective relaying, breaker and switching arrangements, ground sources (zero sequence), ground resistance (Project to remote earth), and assumed line parameters for and Project tie lines.

O Character and the second of						-,			
2. Shunt capacitors associated with the Project	t for power fa	actor correc k							kVars
3. Step-up transformer nominal voltage [(kV)], impedance	۱ د	%	<u></u>		MVA],
MVA rating(s) [MVA],		cal configuration				•	.],
and taps and tap range [141 47 (],	une electri		(o.g.,uona	1170/ [1
4. Station service load (both and kW and KVA	P) and the t	no of load	(e.a. 70% n	votors and 20% h	neating)				1.
kW	in) and the ty	ype or load	k\		reaurig).				Load
5. The following machine data:				<u>.</u>					Load
J. The following machine data.	MVA	Machir	ne base ratin	g on which the d	ata is on (f	for each u	nit)		
	KV	Rated	KV						
	P.F.	Power	factor of ma	chine					
	Н	Inertia	constant of	he machine, MV	V-sec./MVA	١			
	Ra	Armatı	ire resistanc	e, pu					
	Xd	Direct	Direct axis unsaturated synchronous reactance,pu						
Xq Quadrature axis unsaturated synchronous reactance, pu				ı					
	X'd Direct axis unsaturated transient reactance								
	X'q	Quadra	ature axis ur	saturated transie	ent reactan	се			
	X"d	Direct	axis unsatur	ated subtransien	t reactance	;			
	XI	Stator	leakage rea	ctance					
	T'do	Direct	axis transier	t open circuit tim	e constant	, sec			
	T'qo	Quadra	ature axis tra	nsient open circ	uit time cor	nstant, sed			
	T"do	Direct	axis subtran	sient open circuit	time cons	tant, sec			
	T"qo	Quadra	ature axis su	btransient open	circuit time	constant,	sec		
	P max	Maxim	um power o	tput of the turbir	ne in MW				
	S(1.0)	Machir	e data at 1.	per unit of rated	d voltage				
	S(1.2)	Machir	ne data at 1.	2 per unit of rate	d voltage				
6. The type of exciter, block diagram, and para	meters in IEE	EE, PTI or \	VSCC forma	t.					
7. The type of power system stabilizer, block					nat.				
8. The type of governor and turbine, block dia	gram and pa	rameters ir	IEEE,PTI o	WSCC format.					
9. The turbine frequency versus time operation									
To be filled out by the BPA Transmission Accou	nt Executive:								
Transmission Account Executive			Regio	1					
Internal Routing			Phone	Number					
Copy of Interconnection Study Request and Atta Transmission Planning Manager - TOP System Protection Manager - TNC Customer Service Engineering - TOC	achments to:								